


2 FLUTE, DIAMOND COATING BALL NOSE

- High performance on **graphite**, wrought aluminum, bakelite, plastics, wood, brass etc.

Gseries



EDP. No.	D	R	L ₁	L ₂	L ₃	D ₂	D ₃	STOCK
G00501003	0.5	0.25	1	3	50	0.45	4	•
G00501006				6				•
G00501010				10				•
G00601203	0.6	0.3	1.2	3	50	0.55	4	•
G00601206				6				•
G00601208				8				•
G00601210				10				•
G00601212				12				•
G0080164	0.8	0.4	1.6	4	50	0.75	4	•
G0080166				6				•
G0080168				8				•
G0100306	1	0.5	3	6	60	0.95	4	•
G0100308				8				•
G0100310				10				•
G0100312				12				•
G0100314				14				•
G0100316				16				•
G0100318				18				•
G0100320				20				•
G0120410				1.2				0.6
G0150510	1.5	0.75	5	10	60	1.45	4	•
G0150512				12				•
G0150516				16				•
G0150520				20	70			•
G0150525				25				•
G0150530				30				•




2 FLUTE, DIAMOND COATING BALL NOSE

- High performance on **graphite**, wrought aluminum, bakelite, plastics, wood, brass etc.

Gseries



EDP. No.	D	R	L ₁	L ₂	L ₃	D ₂	D ₃	STOCK	
G0200812	2	1	8	12	60	1.95	4	•	
G0200816				16				•	
G0200820				20				•	
G0200825				25	70			•	
G0200830				30				•	
G0200835				35	80			•	
G0200840				40				•	
G0201020				10	20			80	•
G0201020L								100	•
G0251020				2.5	1.25			10	20
G0301216	3	1.5	12	16	60	2.9	6	•	
G0301220				20				70	•
G0301225				25				•	
G0301230				30	80			•	
G0301235				35				•	
G0301240				40	90			•	
G0301245				45				•	
G0301525				15	25			80	4
G04015S	4	2	15	-	50	-	4	•	
G04015M				-	80	-		•	
G04015L				-	120	-		•	
G0401520				20	60	3.9	6	•	
G0401525				25	70			•	
G0401530				30	80			•	
G0401535				35				•	
G0401540				40	90			•	
G0401545				45				•	
G0401550				50	100			•	
G0402030				20	30			80	4



2 FLUTE, DIAMOND COATING BALL NOSE

- High performance on **graphite**, wrought aluminum, bakelite, plastics, wood, brass etc.

Gseries



EDP. No.	D	R	L ₁	L ₂	L ₃	D ₂	D ₃	STOCK	
G0503050	5	2.5	30	50	100	4.8	6	•	
G0503050L					150			•	
G06020S	6	3	20	-	70	-	6	•	
G06020M					100			•	
G06020L					150			•	
G0603050			30	50	-	100		5.8	•
G0603050L						150			•
G08025S	8	4	25	-	70	-	8	•	
G08025M					110			•	
G08025L					160			•	
G0804060			40	60	-	110		7.8	•
G0804060L						200			•
G10030S	10	5	30	-	80	-	10	•	
G10030M					120			•	
G10030L					170			•	
G1005070			50	70	-	120		9.7	•
G1005070L						200			•
G12035S	12	6	35	-	80	-	12	•	
G12035M					130			•	
G12035L					180			•	
G1205575			55	75	-	130		11.7	•
G1205575L						200			•

■ Tolerance

Mill Dia. (mm)	Shank Dia.
0 ~ -0,03	h6

※Items can be changed for quality improvement without notice.