



2 FLUTE, REGULAR LENGTH

- Designed to machine tool steel, alloy steel, mold steel and other high hardened materials.
- Excellent high-performance Endmills.

TX302...series



EDP. No.	Dia.	L ₁	L ₂	D ₂	STOCK
TX302010	1	3	50	4	•
TX302015	1.5	4	50	4	•
TX302020	2	6	50	4	•
TX302025	2.5	8	50	4	•
TX302030	3	9	50	4	•
TX302040	4	11	50	4	•
TX302050	5	13	50	6	•
TX302060	6	16	50	6	•
TX302070	7	16	60	8	•
TX302080	8	19	60	8	•
TX302090	9	19	60	10	•
TX302100	10	25	75	10	•
TX302120	12	30	75	12	•
TX302140	14	32	75	14	•
TX302160	16	32	100	16	•
TX302180	18	32	100	18	•
TX302200	20	38	100	20	•

■ Tolerance μm = 1/1000mm

Tolerance \ Dia.	from 1 to 3	over 3 to 6	over 6 to 10	over 10 to 18	over 18 to 30
Cutting Edge(d11)	-14 -28	-20 -38	-25 -47	-32 -59	-40 -73
Shank(h6)	0 -6	0 -8	0 -9	0 -11	0 -13