



38° HELIX ROUGHING ENDMILL-FOR ALUMINUM

ROUGHING ENDMILL - for Aluminum
DIN6527L / DIN6535-HA, DIN6535-HB

- Suitable for Aluminum, Aluminum Alloy, Copper & Non-Ferrous Material

WAF303 ...series



EDP NO.	DIAMETER	CUTTING LENGTH	OVERALL LENGTH	SHANK DIAMETER
	D	L1	L2	D2
WAF303 040	4	10	55	6
WAF303 050	5	15	55	6
WAF303 060	6	16	60	6
WAF303 061	6	25	80	6
WAF303 070	7	16	63	8
WAF303 080	8	20	65	8
WAF303 081	8	30	90	8
WAF303 090	9	19	72	10
WAF303 100	10	25	75	10
WAF303 101	10	40	100	10
WAF303 120	12	30	80	12
WAF303 121	12	50	110	12
WAF303 140	14	35	90	14
WAF303 160	16	42	100	16
WAF303 161	16	52	150	16
WAF303 162	16	65	125	16
WAF303 180	18	32	92	18
WAF303 200	20	38	104	20
WAF303 201	20	55	160	20

※ Flat Shank is available upon request
ex) WAF303100F

■ Tolerance $\mu\text{m} = 1/1000\text{mm}$

Tolerance \ Dia.	from 1 to 3	over 3 to 6	over 6 to 10	over 10 to 18	over 18 to 30
Cutting Edge(h10)	0 -40	0 -48	0 -58	0 -70	0 -84
Shank(h6)	0 -6	0 -8	0 -9	0 -11	0 -13

※ Items can be changed for quality improvement without notice.