


2 FLUTE, CORNER RADIUS WITH D,L,C COATED-FOR ALUMINUM & NONFERROUS

2 FLUTE, CORNER RADIUS, LONG LENGTH,D.L.C. COATING

- Suitable for Aluminum, Aluminum Alloy, Copper & Non-Ferrous Material
- Adjust Corner Radius to prevent chipping (Not applicable for R Shape machining)
- Diamond Film Coating maximizes the tool life.

WAR502 ...series



EDP NO.	DIAMETER	CORNER RADIUS	CUTTING LENGTH	NECK LENGTH	SHANK DIAMETER
	D	R	L ₁	L ₂	D ₂
WAR502 010	1	0.05	3	40	6
WAR502 015	1.5	0.05	5	40	6
WAR502 020	2	0.1	6	40	6
WAR502 021	2	0.1	12	50	6
WAR502 030	3	0.1	10	50	6
WAR502 031	3	0.1	20	60	6
WAR502 040	4	0.1	12	50	6
WAR502 041	4	0.1	20	60	6
WAR502 050	5	0.1	15	57	6
WAR502 060	6	0.1	15	57	6
WAR502 061	6	0.1	22	65	6
WAR502 070	7	0.1	20	63	8
WAR502 080	8	0.1	20	63	8
WAR502 081	8	0.1	28	70	8
WAR502 090	9	0.1	25	72	10
WAR502 100	10	0.2	28	72	10
WAR502 101	10	0.2	32	80	10
WAR502 110	11	0.2	30	80	12
WAR502 120	12	0.2	32	80	12
WAR502 121	12	0.2	40	100	12

■ Tolerance

Mill Dia. (mm)	Shank dia.
0 ~ -0,02	h6

※ Items can be changed for quality improvement without notice.