



## **5 FLUTES, STUB CUT LENGTH**

- Maintains Cutting Edge Strength & Sharpness for Improved Tool Life
- Strong Cutting Edges Allowing for Increased depths of cut at Elevated Cutting Speeds & Feeds
- Higher Feeds and Speeds for increased Productivity. Reduced Vibration Harmonics.

## XE505A ... series











| EDP. No.    | D    | Li   | L <sub>2</sub> | D <sub>2</sub> | STOCK |
|-------------|------|------|----------------|----------------|-------|
| XE505 A 016 | 1/4  | 3/8  | 2              | 1/4            | •     |
| XE505 A 020 | 5/16 | 7/16 | 2              | 5/16           | •     |
| XE505 A 024 | 3/8  | 1/2  | 2              | 3/8            | •     |
| XE505 A 028 | 7/16 | 9/16 | 2-1/2          | 7/16           | •     |
| XE505 A 032 | 1/2  | 5/8  | 2-1/2          | 1/2            | •     |
| XE505 A 040 | 5/8  | 3/4  | 3              | 5/8            | •     |
| XE505 A 048 | 3/4  | 1    | 3              | 3/4            | •     |
| XE505 A 064 | 1    | 1    | 4              | 1              | •     |

## ■ Tolerance

| Mill Dia. (in      | Shank Dia. |            |  |  |  |
|--------------------|------------|------------|--|--|--|
| from 1/8 up to 1/4 | 0 ~0012    | 0001 ~0003 |  |  |  |
| over 1/4 up to 3/8 | 0 ~0016    |            |  |  |  |
| over 3/8 up to 1   | 0 ~002     | 0001 ~0004 |  |  |  |
|                    |            |            |  |  |  |

»Items can be changed for quality improvement without notice,