


4 FLUTE, STUB CUT LENGTH with EXTENDED NECK

- High precision and excellent surface due to each 4F broken index geometry
- The unique patented design decrease chatter and resonance, can achieve an Axial Depth 1XD
- Sharp cutting edge geometry designed for excellent performance on mild mold steel and stainless steel
- * corner chamfer type

XE514 ...series



EDP. No.	D	L ₁	L ₂	L ₃	D ₂	D ₃	STOCK
XE514010	1	2	10	45	0.8	4	•
XE514020	2	3	12	45	1.8	4	•
XE514030	3	4	14	50	2.8	6	•
XE514040	4	5	16	50	3.8	6	•
XE514050	5	6	18	50	4.8	6	•
XE514060	6	7	20	50	5.8	6	•
XE514080	8	9	26	60	7.8	8	•
XE514100	10	11	31	70	9.8	10	•
XE514120	12	13	37	75	11.8	12	•
XE514160	16	17	43	90	15.8	16	•
XE514200	20	21	53	100	19.8	20	•

※ Flat shank is available upon request
ex) XE514100F : Flat shank

■ Tolerance

Mill Dia. (mm)		Shank Dia.
Diameter	Tolerance	
up to 12	0 ~ -0.02	h6
over 12	0 ~ -0.03	

※Items can be changed for quality improvement without notice.