



### 2 FLUTE, REGULAR LENGTH

- Designed to machine tool steel, alloy steel, mold steel and other high hardened materials.

## ZE302 ...series



EDP. No.	Dia.	L <sub>1</sub>	L <sub>2</sub>	D <sub>2</sub>	STOCK
ZE302010	1	2.5	40	6	•
ZE302015	1.5	4	40	6	•
ZE302020	2	6	40	6	•
ZE302025	2.5	8	40	6	•
ZE302030	3	8	45	6	•
ZE302035	3.5	10	45	6	•
ZE302040	4	11	45	6	•
ZE302045	4.5	11	45	6	•
ZE302050	5	13	50	6	•
ZE302055	5.5	13	50	6	•
ZE302060	6	13	50	6	•
ZE302065	6.5	16	60	8	•
ZE302070	7	16	60	8	•
ZE302075	7.5	16	60	8	•
ZE302080	8	19	60	8	•
ZE302085	8.5	19	70	10	•
ZE302090	9	19	70	10	•
ZE302095	9.5	19	70	10	•
ZE302100	10	22	70	10	•
ZE302105	10.5	22	75	12	•
ZE302110	11	22	75	12	•
ZE302115	11.5	22	75	12	•
ZE302120	12	26	75	12	•
ZE302130	13	26	80	12	•
ZE302140	14	26	80	14	•
ZE302150	15	32	90	16	•
ZE302160	16	32	90	16	•
ZE302180	18	32	100	18	•
ZE302200	20	38	100	20	•

■ Tolerance

Mill Dia, (mm)	Shank Dia,
0 ~ -0,02	h6

※Items can be changed for quality improvement without notice.