



### 6 FLUTE, REGULAR & LONG LENGTH

- Designed for highly hardened materials up to HRc 55.
- Suitable for high speed & finishing machining.

## ZE506 ...series



EDP. No.	Dia.	L <sub>1</sub>	L <sub>2</sub>	D <sub>2</sub>	STOCK
ZE506060	6	15	50	6	•
ZE506061		26	70		•
ZE506070	7	18	60	8	•
ZE506080	8	18	60	8	•
ZE506081		36	90		•
ZE506090	9	22	70	10	•
ZE506100	10	22	70	10	•
ZE506101		46	100		•
ZE506110	11	26	75	12	•
ZE506120	12	26	75	12	•
ZE506121		56	110		•
ZE506130	13	32	85	14	•
ZE506140	14	32	85	14	•
ZE506150	15	35	90	16	•
ZE506160	16	35	90	16	•
ZE506161		66	130		•
ZE506180	18	44	100	18	•
ZE506200	20	44	100	20	•
ZE506201		76	150		•
ZE506250	25	50	120	25	•
ZE506251		92	180		•
ZE506320	32	70	150	32	•

■ Tolerance

Mill Dia. (mm)	Shank Dia.
0 ~ -0,03	h6

※Items can be changed for quality improvement without notice.