



**4 FLUTE, 45° HELIX STUB CUT LENGTH, CORNER RADIUS with EXTENDED NECK**

- Designed for high hardened materials up to HRc 45.
- Suitable for high speed machining.

**ZR304H ...series**



EDP. No.	D	R	L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	D <sub>2</sub>	D <sub>3</sub>	STOCK
ZR304H0303	3	0.3	4	12	55	2.8	6	
ZR304H0305		0.5						
ZR304H0403	4	0.3	5	16	55	3.8	6	
ZR304H0405		0.5						
ZR304H0605	6	0.5	7	20	60	5.8	6	
ZR304H0610		1.0						
ZR304H0805	8	0.5	10	25	65	7.8	8	
ZR304H0810		1.0						
ZR304H1005	10	0.5	12	30	70	9.8	10	
ZR304H1010		1.0						
ZR304H1015		1.5						
ZR304H1020		2.0						
ZR304H1205	12	0.5	15	30	80	11.8	12	
ZR304H1210		1.0						
ZR304H1215		1.5						
ZR304H1220		2.0						

※ These tools are manufactured based on order received.

■ Tolerance

Mill Dia, (mm)	Shank Dia,
0 ~ -0,03	h6

※ Items can be changed for quality improvement without notice.