


### 2 FLUTE, LONG LENGTH, CORNER RADIUS

- Designed to machine tool steel, alloy steel, mold steel and other high hardened materials.
- Superior workpiece finishes.
- Increased feed rate.

## ZR522 ...series



EDP. No.	Dia.	R	L <sub>1</sub>	L <sub>2</sub>	D <sub>2</sub>	STOCK
ZR5220302S4	3	0.2	8	60	4	•
ZR5220302					6	•
ZR5220305S4		0.5			4	•
ZR5220305					6	•
ZR5220402S4	4	0.2	11	70	4	•
ZR5220402	4	0.2	11	70	6	•
ZR5220405S4		0.5			4	•
ZR5220405		0.5			6	•
ZR5220410		1			6	•
ZR5220502	5	0.2	13	80	6	•
ZR5220505		0.5				•
ZR5220510		1				•
ZR5220602	6	0.2	13	90	6	•
ZR5220605		0.5				•
ZR5220610		1				•
ZR5220805	8	0.5	19	100	8	•
ZR5220810		1				•
ZR5220815		1.5				•
ZR5220820		2				•
ZR5221005	10	0.5	22	100	10	•
ZR5221010		1				•
ZR5221015		1.5				•
ZR5221020		2				•
ZR5221025		2.5				•
ZR5221205	12	0.5	26	110	12	•
ZR5221210		1				•
ZR5221215		1.5				•
ZR5221220		2				•
ZR5221225		2.5				•
ZR5221230		3				•

■ Tolerance

Mill Dia. (mm)	Shank Dia.
0 ~ -0,02	h6

※ Items can be changed for quality improvement without notice.