


2 FLUTE, 45° HELIX-FOR ALUMINUM
 2 FLUTE, REGULAR LENGTH for Aluminum

– Suitable for Aluminum, Aluminum Alloy, Copper & Non-ferrous material

WAE302 ...series




| EDP NO. | DIAMETER | CUTTING LENGTH | OVERALL LENGTH | SHANK DIAMETER |
|---------------|----------|----------------|----------------|----------------|
| | D | L1 | L2 | D2 |
| WAE302 010 | 1 | 3 | 50 | 4 |
| WAE302 010-6 | 1 | 6 | 60 | 6 |
| WAE302 012 | 1,2 | 4 | 50 | 6 |
| WAE302 015 | 1,5 | 6 | 50 | 6 |
| WAE302 015-8 | 1,5 | 8 | 60 | 6 |
| WAE302 020 S4 | 2 | 6 | 50 | 4 |
| WAE302 025 | 2,5 | 12 | 55 | 6 |
| WAE302 030 | 3 | 12 | 55 | 6 |
| WAE302 030-15 | 3 | 15 | 65 | 6 |
| WAE302 035 | 3,5 | 14 | 57 | 6 |
| WAE302 040 | 4 | 14 | 55 | 6 |
| WAE302 040-16 | 4 | 16 | 65 | 6 |
| WAE302 050 | 5 | 17 | 55 | 6 |
| WAE302 050-22 | 5 | 22 | 60 | 6 |
| WAE302 060 | 6 | 17 | 60 | 6 |
| WAE302 060-22 | 6 | 22 | 60 | 6 |
| WAE302 070 | 7 | 20 | 63 | 8 |
| WAE302 080 | 8 | 23 | 70 | 8 |
| WAE302 080-31 | 8 | 31 | 80 | 8 |
| WAE302 090 | 9 | 25 | 72 | 10 |
| WAE302 100 | 10 | 28 | 75 | 10 |
| WAE302 100-36 | 10 | 36 | 90 | 10 |
| WAE302 110 | 11 | 30 | 80 | 12 |
| WAE302 120 | 12 | 33 | 80 | 12 |
| WAE302 120-41 | 12 | 41 | 95 | 12 |

■ Tolerance

| Mill Dia.(mm) | Shank Dia. |
|---------------|------------|
| 0 ~ -0,02 | h6 |


※ Items can be changed for quality improvement without notice



2 FLUTE, 45° HELIX-FOR ALUMINUM
2 FLUTE, REGULAR LENGTH for Aluminum

– Suitable for Aluminum, Aluminum Alloy, Copper & Non-ferrous material

WAE302 ...series



| EDP NO. | DIAMETER | CUTTING LENGTH | OVERALL LENGTH | SHANK DIAMETER |
|---------------|----------|----------------|----------------|----------------|
| | D | L1 | L2 | D2 |
| WAE302 122 | 12 | 45 | 100 | 12 |
| WAE302 130 | 13 | 35 | 85 | 14 |
| WAE302 140 | 14 | 38 | 90 | 14 |
| WAE302 150 | 15 | 40 | 90 | 16 |
| WAE302 160 | 16 | 45 | 100 | 16 |
| WAE302 160-53 | 16 | 53 | 110 | 16 |
| WAE302 180 | 18 | 49 | 100 | 18 |
| WAE302 200 | 20 | 50 | 100 | 20 |
| WAE302 200-55 | 20 | 55 | 110 | 20 |
| WAE302 250 | 25 | 50 | 120 | 25 |

■ Tolerance

| Mill Dia.(mm) | Shank Dia. |
|---------------|------------|
| 0 ~ -0.02 | h6 |

※ Items can be changed for quality improvement without notice