


3 FLUTE, REGULAR LENGTH

- High precision and excellent surface due to each 4F broken index geometry
 - The unique patented design decrease chatter and resonance, can achieve an Axial Depth 1XD
 - Reinforced bending moment because of double core geometry
- * corner chamfer type

XCC503 ...series



EDP. No.	D	C	L ₁	L ₂	D ₂	STOCK
XCC503020	2	0.025	6	50	6	•
XCC503025	2.5	0.025	8	50	6	•
XCC503030	3	0.035	10	50	6	•
XCC503035	3.5	0.035	10	50	6	•
XCC503040	4	0.045	12	50	6	•
XCC503045	4.5	0.045	14	50	6	•
XCC503050	5	0.055	15	50	6	•
XCC503055	5.5	0.055	15	50	6	•
XCC503060	6	0.075	15	50	6	•
XCC503080	8	0.1	20	60	8	•
XCC503100	10	0.125	25	70	10	•
XCC503120	12	0.150	30	75	12	•
XCC503160	16	0.200	40	90	16	•
XCC503200	20	0.250	45	100	20	•
XCC503250	25	0.300	50	120	25	•

※ Flat shank is available upon request
ex) XCC503100F : Flat shank

■ Tolerance

Mill Dia, (mm)	Shank Dia,
0 ~ -0,02	h6

※Items can be changed for quality improvement without notice.