



5 FLUTES, REGULAR CUT LENGTH WITH EXTENDED NECK

- Maintains Cutting Edge Strength & Sharpness for Improved Tool Life
- Strong Cutting Edges Allowing for Increased depths of cut at Elevated Cutting Speeds & Feeds
- Higher Feeds and Speeds for increased Productivity. Reduced Vibration Harmonics.

XR525A ... series



EDP. No.	D	R	L ₁	L ₂	L ₃	D ₂	D ₃	STOCK
XR525 A 016 015	1/4	.015	3/4	2-1/8	4	.242	1/4	•
XR525 A 016 030		.030						•
XR525 A 020 015	5/16	.015	1	2-1/8	4	.305	5/16	•
XR525 A 020 030		.030						•
XR525 A 024 015	3/8	.015	1	2-1/8	4	.367	3/8	•
XR525 A 024 030		.030						•
XR525 A 028 015	7/16	.015	-1/4	2-1/8	4	.430	7/16	•
XR525 A 028 030		.030						•
XR525 A 032 015	1/2	.015	1-1/4	2-1/8	4	.492	1/2	•
XR525 A 032 030		.030						•
XR525 A 032 015L		.015	1-3/8	3-1/8	5			•
XR525 A 032 030L		.030						•
XR525 A 040 015	5/8	.015	1-1/2	2-1/8	4	.617	5/8	•
XR525 A 040 030		.030						•
XR525 A 040 045		.045						•
XR525 A 040 015L		.015	1-3/4	3-1/8	5			•
XR525 A 040 030L		.030						•
XR525 A 040 045L		.045						•
XR525 A 048 015	3/4	.015	1-7/8	3	5	.742	3/4	•
XR525 A 048 030		.030						•
XR525 A 048 045		.045						•
XR525 A 064 015	1	.015	2-1/4	3	5	.992	1	•
XR525 A 064 030		.030						•
XR525 A 064 045		.045						•

■ Tolerance

Mill Dia. (inch)		Shank Dia.
from 1/8 up to 1/4	0 ~ -.0012	-.0001 ~ -.0003
over 1/4 up to 3/8	0 ~ -.0016	
over 3/8 up to 1	0 ~ -.002	-.0001 ~ -.0004

※Items can be changed for quality improvement without notice.