



2 FLUTE, REGULAR LENGTH

- Designed to machine tool steel, alloy steel, mold steel and other high hardened materials.
- Superior workpiece finishes.

ZE502 ...series



EDP. No.	Dia.	L1	L2	D2	STOCK
ZE502010	1	3	42	4	•
ZE502010				6	•
ZE502015	1.5	4	42	6	•
ZE502020				4	•
ZE502020	2	6	42	6	•
ZE502025				6	•
ZE502025	2.5	8	42	6	•
ZE502030				4	•
ZE502030	3	10	50	6	•
ZE502035				6	•
ZE502040	4	12	50	4	•
ZE502040				6	•
ZE502045	4.5	14	50	6	•
ZE502050	5	15	50	6	•
ZE502055	5.5	15	50	6	•
ZE502060	6	15	50	6	•
ZE502065	6.5	18	60	8	•
ZE502070	7	20	60	8	•
ZE502075	7.5	20	60	8	•
ZE502080	8	20	60	8	•
ZE502085	8.5	23	70	10	•
ZE502090	9	25	70	10	•
ZE502095	9.5	25	70	10	•
ZE502100	10	25	70	10	•
ZE502105	10.5	28	75	12	•
ZE502110	11	30	75	12	•
ZE502115	11.5	30	75	12	•
ZE502120	12	30	75	12	•
ZE502125S12	12.5	30	80	12	•
ZE502130S12	13	30	80	12	•
ZE502130			85	14	•
ZE502130S16			90	16	•
ZE502140	14	35	85	14	•
ZE502140S16			90	16	•
ZE502150			90	16	•
ZE502160	15	40	90	16	•
ZE502170	16	40	90	16	•
ZE502170	17	40	100	16	•
ZE502180	18	45	100	18	•
ZE502190	19	45	100	20	•
ZE502200	20	45	100	20	•
ZE502220	22	45	100	20	•
ZE502240	24	50	120	25	•
ZE502250	25	50	120	25	•

■ Tolerance

Mill Dia, (mm)	Shank Dia,
0 ~ -0,02	h6

※Items can be changed for quality improvement without notice.