


### 2 FLUTE, REGULAR LENGTH, CORNER RADIUS

- Designed to machine tool steel, alloy steel, mold steel and other high hardened materials.
- Superior workpiece finishes.
- Increased feed rate.

## ZR512 ...series



EDP. No.	Dia.	R	L <sub>1</sub>	L <sub>2</sub>	D <sub>2</sub>	STOCK
ZR5120605	6	0.5	15	55	6	•
ZR5120610		1				•
ZR5120805	8	0.5	20	65	8	•
ZR5120810		1				•
ZR5120815		1.5				•
ZR5120820		2				•
ZR5121005	10	0.5	25	80	10	•
ZR5121010		1				•
ZR5121015		1.5				•
ZR5121020		2				•
ZR5121025		2.5				•
ZR5121030	3	•				
ZR5121205	12	0.5	30	82	12	•
ZR5121210		1				•
ZR5121215		1.5				•
ZR5121220		2				•
ZR5121225		2.5				•
ZR5121230	3	•				
ZR5121605	16	0.5	40	100	16	•
ZR5121610		1				•
ZR5121615		1.5				•
ZR5121620		2				•
ZR5121630	3	•				
ZR5122005	20	0.5	45	110	20	•
ZR5122010		1				•
ZR5122015		1.5				•
ZR5122020		2				•
ZR5122030		3				•

■ Tolerance

Mill Dia, (mm)	Shank Dia,
0 ~ -0,03	h6

※Items can be changed for quality improvement without notice.