


Пластины формы S (90°)



Форморазмер	IC	S	D1
SN_1204_	12.7	4.76	5.16
SN_1506_	15.875	6.35	6.35
SN_1906_	19.05	6.35	7.94
SN_2507_	25.4	7.94	9.12
SN_2509_	25.4	9.52	9.12
SN_3109_	31.75	9.52	9.45

Пластины и вид обработки	Обозначение пластины	RE (мм)	Режимы резания		Условия обработки																					
					● Хорошие			● Средние			● Плохие			●												
					p					M				K		N		S								
f (мм/об)	ap (мм)	AT202	AC052P	AC152P	AC252P	AC350P	AC100M	AC200M	AP200U	AP301M	AC100K	AC102K	AC202K	AW100K	AP100S											
Черновая обработка	SNMA 120408E-KD5	0.8	0.20-0.60	1.20-6.4												●	●	●								
	120412E-KD5	1.2	0.30-0.90	1.80-6.4												●	●	●								
	120416E-KD5	1.6	0.40-1.20	2.40-6.4												●	●	●								
	150612E-KD5	1.2	0.30-0.90	1.80-7.9													●	●	●							
	150616E-KD5	1.6	0.40-1.20	2.40-7.9													●	●	●							
	190612E-KD5	1.2	0.30-0.90	1.80-9.5														●	●	●						
	190616E-KD5	1.6	0.40-1.20	2.40-9.5														●	●	●						
Тяжёлая черновая обработка	SNMM 120408E-PD8	0.8	0.16-0.32	1.44-5.1			▲	▲	●																	
	120412E-PD8	1.2	0.24-0.48	2.16-5.1			▲	▲	●																	
	150612E-PD8	1.2	0.24-0.48	2.16-6.4			▲	▲	●																	
	150616E-PD8	1.6	0.32-0.64	2.88-6.4	●		▲	▲	●																	
	190612E-PD8	1.2	0.24-0.48	2.16-7.6			▲	▲	●																	
	190616E-PD8	1.6	0.32-0.64	2.88-7.6	●		▲	▲	●																	
	190624E-PD8	2.4	0.48-0.96	4.32-7.6	●		▲	▲	●																	
	250724E-PD8	2.4	0.48-0.96	4.32-10.2			▲	▲	●																	
	250924E-PD8	2.4	0.48-0.96	4.32-10.2			▲	▲	●																	
	SNMM 190612S-PC9	1.2	0.26-0.60	2.40-9.5			▲	▲																		
	190616S-PC9	1.6	0.35-0.80	3.20-9.5			▲	▲	●																	
	190624S-PC9	2.4	0.53-1.20	4.80-9.5			▲	▲	●																	
	250724S-PC9	2.4	0.53-1.20	4.80-12.7			▲	▲	●																	
	250924S-PC9	2.4	0.53-1.20	4.80-12.7			▲	▲	●																	
	SNMH 310924S-PC9	2.4	0.53-1.20	4.80-15.9				▲	●																	
	SNMM 190612S-PD9	1.2	0.30-0.72	2.64-11.4			▲	▲	●																	
	190616S-PD9	1.6	0.40-0.96	3.52-11.4			▲	▲	●																	
	190624S-PD9	2.4	0.60-1.44	5.28-11.4			▲	▲	●																	
	250724S-PD9	2.4	0.60-1.44	5.28-15.2			▲	▲	●																	
	250924S-PD9	2.4	0.60-1.44	5.28-15.2			▲	▲	●																	
	SNMX 310924S-PD9	2.4	0.60-1.44	5.28-19.1				▲	●																	

● : На складе ▲ : На складе, но скоро выйдет замена.