









Державки для наружного точения

Типы оснастки	Кат. №	Наличие		Размеры (мм)							Станд. радиус при вершине r_{ϵ}	Применяемые пластины	Форма			
		R	L	h	b	L ₁	L ₂	h ₁	f	f ₂						
Наружное профилирование MDJNR/L  Исполнение режущей кромки J	MDJNR/L1616H11			16	16	100	30	16	20	—	0.8	DN□□1104□□ 55°/6° ➤2-52 ~	 Показано правое исполнение R			
	MDJNR/L2020K15			20	20	125		20	25			DN□□1504□□ 55°/6° 55°/6°				
	MDJNR/L2525M15	●		25		150		25				0.8		DN□□1506□□ 55°/6° ➤2-52 ~		
	MDJNR/L3225P15				25		38		32	19		T-CBN ➤3-7 ~ T-DIA ➤3-21 ~				
	MDJNR/L3232P15				32		170		32		40					
	MDJNR/L2020K15C			20	20	125		20	25					DN□□1507□□ 55°/6° ➤2-60 ~		
	MDJNR/L2525M15C			25		150		25				19		0.8	DN□□1506□□ 55°/6° ➤2-52 ~	
	MDJNR/L3225P15C				32		170		32			40				
	MDJNR/L3232P15C				32		170		32		40					
Профилирование MDQNR/L  Исполнение режущей кромки Q	MDQNR/L1616H11			16	16	100	30	16	20	—	0.8	DN□□1104□□ 55°/6° ➤2-52 ~	 Показано правое исполнение R			
	MDQNR/L2020K15			20	20	125		20	25					DN□□1504□□ 55°/6° 55°/6°		
	MDQNR/L2525M15			25		150		25						0.8	DN□□1506□□ 55°/6° ➤2-52 ~	
	MDQNR/L3225P15				32		170		32		40			T-CBN ➤3-7 ~ T-DIA ➤3-21 ~		
	MDQNR/L3232P15				32		170		32		40					
Наружное профилирование MDPNN  Исполнение режущей кромки P	MDPNN1616H11			16	16	100	36	16	8		0.8	DN□□1104□□ 55°/6° ➤2-52 ~	 Показано правое исполнение R			
	MDPNN2020K15			20	20	125		20	10					DN□□1504□□ 55°/6° 55°/6°		
	MDPNN2525M15	●		25		150		25						0.8	DN□□1506□□ 55°/6° ➤2-52 ~	
	MDPNN3225P15				32		170		32		12.5			T-CBN ➤3-7 ~ T-DIA ➤3-21 ~		
	MDPNN3232P15				32		170		32		16					
Наружное профилирование MTJNR/L  Исполнение режущей кромки J	MTJNR/L2020K16			20	20	125		20	25				TN□□1603□□ TN□□1604□□ 60°/6° 60°/6° ➤2-70 ~	 Показано правое исполнение R		
	MTJNR/L2525M16	●		25		150	28	25					0.8		➤2-70 ~	
	MTJNR/L3225P16				25				32						T-CBN ➤3-8 ~ T-DIA ➤3-21 ~	
	MTJNR/L2525M22			25		150		25							0.8	TN□□2204□□ 60°/6° 60°/6° ➤2-70 ~
	MTJNR/L3225P22				32		170		32							
	MTJNR/L3232P22				32		170		32		40					
	MTJNR/L3232P22				32		170		32		40					

● : Складские позиции